

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2859015

Beverly Hills Non-Skid Gray**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 04/17/98

HEALTH 2
FLAMMABILITY 2

REACTIVITY 0

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Calcium Napthenate	61789-36-4	No Info	No Info	No Info (TWA)	0.1
Alkanes, Chloro	61788-76-9	No Info	No Info	No Info	1.0
Methane, Tetrachloro	56-23-5	2 PPM	No Info	5 PPM	0.1
Cobalt Napthenate	61789-51-3	0.1 MG/M3	No Info	0.05 MG/M3	0.1
Titanium Dioxide	13463-67-7	No Info	No Info	10 MG/M3	5
Aluminum Hydroxide	21645-51-2	No Info	No Info	No Info	0.1
Amorphous Silica	7631-86-9	No Info	No Info	No Info	0.1
Zirconium Octoate	22464-99-9	No Info	10 MG/M3	5 MG/M3	1.0
P.M. Acetate	108-65-6	No Info	No Info	100 PPM	1.0
Industrial Talc	14807-96-6	2 MG/M3	No Info	2 MG/M3	15
Silicon Dioxide	01-4808-60-7	No Info	No Info	10.1 MG/M3	45
Methyl Ethyl Ketoximine	96-29-7	No Info	No Info	No Info	1.0

Section III Physical Characteristics

Boiling Point	318-390 F	Specific Gravity (Water=1)	N/A
Vapor Pressure	N/A	Melting Point	N/A
Vapor Density	Heavier than air	Evaporation Rate	N/A

Solubility In Water	None
Appearance and Odor	Opaque Gray. Solvent odor.

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
105 F (Tagliabue Closed Cup)		0.7	6.0

Extinguishing Media Carbon Dioxide, Dry Chemical, Foam, Water Fog.