

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

**Identify (Code Number, Name)**

2200947/10

**Bolt Buster Gel****Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, FL 33024**

Emergency Telephone Number  
1-800-228-5635

Telephone # For Information  
1-800-253-3500

Date Prepared: 06/04/96

**HEALTH** 2**FLAMMABILITY** 4**REACTIVITY** 1

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64741-66-8	400 ppm	400 ppm		10-20
Acetone	67-64-1	750 ppm	750 ppm		10-20
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		40-60

**Section III Physical Characteristics**

<b>Boiling Point</b>	140 deg F	<b>Specific Gravity (Water =1)</b>	@ 75 deg F: 0.830
<b>Vapor Pressure</b>	(can/psig @ 70 deg F): 50	<b>Melting Point</b>	
<b>Vapor Density</b>	>1	<b>Evaporation Rate</b>	

<b>Solubility in Water</b>	Moderate
<b>Appearance and Odor</b>	Cloudy liquid, solvent odor

**Section IV Fire and Explosion Hazard Data**

Flash Point	Flammable Limits	LEL	UEL
(Concentrate only): 85 deg F (T.O.C.)	Extremely flammable spray		