

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no.1218-0072

**Identify (Code Number, Name)**

1150435/07

**Chewing Gum & Wax Remover****Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number

1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 08/28/97

**HEALTH** 1**FLAMMABILITY** 4**REACTIVITY** 0

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Hexane	110-54-3	50	50		1-10
Isobutane	75-28-5	---	800		90-100

**Section III Physical Characteristics**

<b>Boiling Point</b>	-11.7 deg F to 159 deg F	<b>Specific Gravity (Water =1)</b>	0.5
<b>Vapor Pressure</b>	PSIG @ 70 deg F - 52	<b>Melting Point</b>	N/A
<b>Vapor Density</b>	4.0	<b>Evaporation Rate</b>	>1
<b>Solubility In Water</b>	Nil		
<b>Appearance and Odor</b>	Clear/solvent		

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
-160 deg F TCC		1.9	8.5

<b>Extinguishing Media</b>	Water fog, dry chemical or carbon dioxide.
----------------------------	--