

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2200260/14

Defense**Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
 1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 10/17/96

HEALTH 1**FLAMMABILITY** 0**REACTIVITY** 0

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Polydimethylsiloxane	63148-62-9	N/E	N/E		05-10
Liquified Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		05-10

Section III Physical Characteristics

Boiling Point	-200 deg F	Specific Gravity (Water =1)	@ 70 deg F: 0.970
Vapor Pressure	(can/psig @ 70 deg F: 60	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A
Solubility In Water	Complete		
Appearance and Odor	Milky White Foam with Mild Odor		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
(Concentrate only): None to boiling (~212 deg F - T.O.C.)	Non-flammable Spray	N/A	N/A