

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200955/14

Dry Moly Lube**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 10/04/95

HEALTH 2
FLAMMABILITY 3

REACTIVITY 0

Protective Equipment
B

| Hazardous Components (Specify Chemical Identity, Common Name) | CAS # | OSHA PEL | ACGIH TLV | Other Recommended Limits | % |
|---|------------|----------|-----------|--------------------------|-------|
| Toluene | 108-88-3 | 100 ppm | 100 ppm | | 05-10 |
| Methylene Chloride | 75-09-2 | 50 ppm | 50 ppm | | 40-60 |
| Liquified Petroleum Gas | 68476-85-7 | 1000 ppm | 1000 ppm | | 20-40 |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

Section III Physical Characteristics

| | | | |
|-----------------------|------------------------------|------------------------------------|--------------------|
| Boiling Point | ~92 deg. F | Specific Gravity (Water =1) | @ 75 deg. F: 1.280 |
| Vapor Pressure | (can) psig (@ 70 deg. F): 50 | Melting Point | |
| Vapor Density | >1 | Evaporation Rate | |

| | |
|----------------------------|--|
| Solubility In Water | Slight |
| Appearance and Odor | Black lustrous coating, Mild sweet odor. |

Section IV Fire and Explosion Hazard Data

| | | | |
|-----------------------------------|-------------------------|------------|------------|
| Flash Point | Flammable Limits | LEL | UEL |
| (Concentrate): 80 deg. F (TOC) | Flammable Spray | | |

Extinguishing Media | Foam, CO2, Dry Media.