

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

1250270

Dust Mop Treatment "B"**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number

1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 03/08/95

HEALTH**FLAMMABILITY****REACTIVITY**

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Hydrotreated Distillate, Light	64742-47-8	100ppm	100ppm		
Light Naphtenic Petroleum Distillate	64742-53-6	5mg/m ³	5mg/m ³		
Heavy Naphtenic Petroleum Distillate	64742-52-5	5mg/m ³	5mg/m ³		
Petroleum Naptha	8052-41-3	500ppm	500ppm		
DOT Shipping Classification: Combustible Liquid NA 1993					

Section III Physical Characteristics

Boiling Point	Approx. 400 Deg. F.	Specific Gravity (Water =1)	<1.0
Vapor Pressure	<10 @ 77 Deg. F.	Melting Point	N/A
Vapor Density	4.8 -5.2	Evaporation Rate	<1.0

Solubility In Water	Negligible
Appearance and Odor	Yellow liquid, characteristic solvent odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
141 Deg. F.		1	7

Extinguishing Media	Water fog, foam, dry chemical or carbon dioxide
----------------------------	---