

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

1107291/92/93

Extreme Impact Grease**Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 09/28/95

HEALTH 1
FLAMMABILITY 1

REACTIVITY 0

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Petroleum Oil Mixture	8002-05-9	5mg/M3 TWA for oil mist	5mg/M3 TWA for oil mist		

Section III Physical Characteristics

Boiling Point	N/A	Specific Gravity (Water =1)	0.8
Vapor Pressure	PSIG @ 70 deg F (Aerosol): N/A	Melting Point	
Vapor Density	12	Evaporation Rate	N/A
Solubility in Water	Negligible		
Appearance and Odor	Dark green gel with oil odor.		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
Projection test (Aerosols) N/A Non-Aerosol: >400 deg F		N/D	N/D