

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200216/12

Inhibit**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-253-3500

Telephone # For Information
1-800-253-3500

Date Prepared: 03/02/98

HEALTH 1
FLAMMABILITY 1
REACTIVITY 0
Protective Equipment
B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64742-46-7	200 ppm	200 ppm		60-80
Food Grade Mineral Oil	8042-47-5	5mg/M3	5mg/M3		10-20
Dipropylene Glycol Monomethyl Ether	34590-94-8	100 ppm	100 ppm		01-05
Carbon Dioxide Propellant	124-38-9	1000 ppm	1000 ppm		01-05

Section III Physical Characteristics

Boiling Point	~300 F	Specific Gravity (Water =1)	0.720
Vapor Pressure	90 (Can)	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A
Solubility In Water	Slight		
Appearance and Odor	Brownish liquid. Solvent odor.		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
(Concentrate only) 216 F (TOC)	Non-Flammable Spray	N/A	N/A

Extinguishing Media	Foam, Dry Media, CO2
Special Fire Fighting	Wear self-contained breathing apparatus and protective clothing. Cool fire-exposed containers to