

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2857522

Liquid Strip Thick**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
 1-800-228-5635

Telephone # For Information
 1-800-253-3500

Date Prepared: 04/07/98

HEALTH 3**FLAMMABILITY** 1**REACTIVITY** 1

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Petroleum Was	64742-43-4	No Info	2 MG/M3	No Info (Stel)	1.0
2 Butoxy Ethanol	111-76-2	50 PPM	25 PPM	No Info (Stel)	5
Methanol	67-56-1	200 PPM	200 PPM	250 PPM (Stel)	15
Methylene Chloride	75-09-2	125 PPM	25 PPM	No Info (Stel)	80
This product contains one or more materials subject to the reporting requirements of Section 313 of the Emergency Planning and the Community Tight-To-Know Acts of 1986 and of 40 CFR 372.					

Section III Physical Characteristics

Boiling Point	148 F	Specific Gravity (Water =1)	N/A
Vapor Pressure	N/A	Melting Point	N/A
Vapor Density	> Air	Evaporation Rate	< Ether

Solubility In Water	Miscible
Appearance and Odor	Clear to hazy with sweet aromatic odor.

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
N.A. (Cleveland Open Cup)		1.1	36.5

Extinguishing Media	Water fog, dry chemical, carbon dioxide
----------------------------	---