

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no.1218-0072

**Identify (Code Number, Name)**

2200765/18

Mr. G

**Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, FL 33024**

Emergency Telephone Number

1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 12/10/98

**HEALTH** 3**FLAMMABILITY** 3**REACTIVITY** 1

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Methylene Chloride	75-09-2	50 ppm	50 ppm		40-60
Toluene	108-88-3	100 ppm	100 ppm		10-20
Methanol	67-56-1	200 ppm	200 ppm		01-05
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		05-10
N/A - Not Applicable					
N/D - Not Determined					
< - Less Than					
> - More Than					

**Section III Physical Characteristics**

<b>Boiling Point</b>	N/D	<b>Specific Gravity (Water =1)</b>	1.132
<b>Vapor Pressure</b>	50	<b>Melting Point</b>	N/A
<b>Vapor Density</b>	>1	<b>Evaporation Rate</b>	N/A

<b>Solubility In Water</b>	Slight
<b>Appearance and Odor</b>	Clear liquid with mild sweet odor

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
(Concentrate): 84 F (T.O.C.)	Extremely flammable spray	N/A	N/A

<b>Extinguishing Media</b>	Foam, CO2, Dry Media
<b>Special Fire Fighting</b>	Wear self-contained breathing apparatus and protective clothing. Cool fire- exposed containers to