

**Material Safety Data Sheet**

May be used to comply with  
 OSHA's Hazard Communication Standard 29 CFR 1910  
 Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form) Form Approved OMB no.1218-0072

**Identify (Code Number, Name)**22091<sup>1</sup>0/12

No Slip - GREY

**Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number  
 1-800-228-5635

Telephone # For Information  
 1-800-253-3500

Date Prepared: 05/29/96

**HEALTH** 2  
**FLAMMABILITY** 4  
**REACTIVITY** 0  
 Protective Equipment  
 1

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Acetone	67-64-1	1000 ppm	750 ppm		20-40
Xylene	1330-20-7	150 ppm	100 ppm		10-20
Toluene	108-88-3	150 ppm	100 ppm		10-20
Clay (Dust Hazard)	1332-58-7	N/E	15mg/m3		0-10
Titanium Oxide (Dust Hazard)	13463-67-7	N/E	10mg/m3		0-10
Amorphous Silica (Dust Hazard)	7631-86-9	N/E	6mg/m3		0-5
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		20-40

**Section III Physical Characteristics**

<b>Boiling Point</b>	-13 Deg. F to 232 Deg. F	<b>Specific Gravity (Water =1)</b>	0.800
<b>Vapor Pressure</b>	65	<b>Melting Point</b>	
<b>Vapor Density</b>	>1	<b>Evaporation Rate</b>	

<b>Solubility In Water</b>	Insoluble
<b>Appearance and Odor</b>	Aerosol Mist, Strong Solvent Odor

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
45 Deg. F T.O.C.	Extremely Flammable		

<b>Extinguishing Media</b>	Foam, CO2, Dry Media, Water Fog
----------------------------	---------------------------------