

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200967/15

Re-Touch White Kwik Dri**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 12/03/96

HEALTH 2**FLAMMABILITY** 3**REACTIVITY** 1

Protective Equipment

1

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Toluene	108-88-3	100 ppm	100 ppm		10-20
1,1,1-Trichloroethane	71-55-6	350 ppm	350 ppm		10-20
Titanium Dioxide	13463-67-3	N/E	N/E		01-05
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		40-60

Section III Physical Characteristics

Boiling Point	169 deg F	Specific Gravity (Water =1)	@ 75 deg F: 1.254
Vapor Pressure	(can/psig @ 70 deg F): 55	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A
Solubility In Water	Negligible		
Appearance and Odor	White liquid, Solvent Odor		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
(Concentrate): 78 deg F	Extremely Flammable Spray	N/A	N/A
Extinguishing Media	Foam, CO2, Dry Media		