

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200945\16

Sani-Lube "A"**Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
 1-800-228-5635

Telephone # For Information
 1-800-253-3500

Date Prepared: 05/26/95

HEALTH 1
FLAMMABILITY 1
REACTIVITY 0
 Protective Equipment
 B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Aliphatic Petroleum Distillates	8042-47-5	5 mg/m3	5 mg/m3		60-80
Liquified Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		20-40

Section III Physical Characteristics

Boiling Point	N/D 8	Specific Gravity (Water =1)	0.840 @ 75 deg. F
Vapor Pressure	42	Melting Point	
Vapor Density	>1	Evaporation Rate	
Solubility in Water	Slight		
Appearance and Odor	Colorless Oily Liquid, Mild Odor		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
365deg F (T.O.C.) (Concentrate only)	Extremely flammable spray		
Extinguishing Media	Foam, CO2, Dry Media.		