

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

**Identify (Code Number, Name)**

2200780/12

**Seize Proof "A" Kwik Dri****Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number  
1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 05/08/95

**HEALTH** 1  
**FLAMMABILITY** 3

**REACTIVITY** 1

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isopararfinic Hydrocarbon	64742-45-9	400 ppm	400 ppm		20-40
Copper Compound	7440-50-8	N/E	N/E		10-20
Liquified Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		40-60

**Section III Physical Characteristics**

<b>Boiling Point</b>	140 deg. F.	<b>Specific Gravity (Water =1)</b>	0/973
<b>Vapor Pressure</b>		<b>Melting Point</b>	
<b>Vapor Density</b>	>1	<b>Evaporation Rate</b>	

<b>Solubility In Water</b>	Slight.
<b>Appearance and Odor</b>	Gray Viscous Liquid. Solvent Odor.

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b> (Of Concentrate Only) 78 deg. F. (T>O>C>)	<b>Flammable Limits</b> Extremely flammable spray	<b>LEL</b>	<b>UEL</b>
---	--	------------	------------

<b>Extinguishing Media</b>	Foam, CO2, Dry Media.
----------------------------	-----------------------