

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2857009

R B E Dark Gray

Section 1 Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 03/29/99

HEALTH 2

FLAMMABILITY 2

REACTIVITY 0

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
P.M. Acetate	108-65-6	No Info	100 PPM	N/A	<1.0
Aromatic Petroleum Distillates	64742-95-6	No Info	No Info	N/A	<20
Trimethylbenzenes	25551-13-7	No Info	25 PPM	N/A	<25
Iron Oxide	1309-37-1	No Info	5 MG/M3	N/A	<10
Carbon Black	1333-86-4	3.5 MG/M3	3.5 MG/M3	N/A	<1.0
Chlorinated Paraffin	61788-76-9	No Info	No Info	N/A	<5
Xylene	1330-20-7	100 PPM	100 PPM	N/A	<5
(Section 313)			150 PPM		
			(STEL)		
Mineral Spirits	64741-92-0	No Info	100 ppm	N/A	<25
			200 ppm		
			(STEL)		

Section III Physical Characteristics

Boiling Point	283-383 F	Specific Gravity (Water =1)	N/A
Vapor Pressure	N/A	Melting Point	N/A
Vapor Density	Heavier than air	Evaporation Rate	Slower than ether

Solubility In Water	None
Appearance and Odor	Gray – Aromatic solvent odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
104 F (Tagliabue closed cup)		0.7%	7.0%

Extinguishing Media	Carbon Dioxide, Dry Chemical, Foam, Water Fog
---------------------	---