

# Material Safety Data Sheet

May be used to comply with  
 OSHA's Hazard Communication Standard 29 CFR 1910  
 Standard must be consulted for specific requirements.

## U.S. Department of Labor

Occupational Safety and Health Administration  
 (Non-Mandatory Form) Form Approved OMB no. 1218-0072

### Identify (Code Number, Name)

2200825/13

Static Guard Kwik Dri

### Section 1 Manufacturer's Name

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number  
 1-800-228-5635  
 Telephone # For Information  
 1-800-253-3500  
 Date Prepared: 04/02/96

**HEALTH** 1  
**FLAMMABILITY** 3  
**REACTIVITY** 0  
 Protective Equipment  
 B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64742-48-9	400ppm	400ppm		40-60
Isopropyl Alcohol	67-63-0	400ppm	400ppm		05-10
Liquefied Petroleum Gas	68476-85-7	1000ppm	1000ppm		40-60

### Section III Physical Characteristics

<b>Boiling Point</b> ~ 180 Deg. F.	<b>Specific Gravity (Water =1)</b> 0.735
<b>Vapor Pressure</b> 50	<b>Melting Point</b>
<b>Vapor Density</b> >1	<b>Evaporation Rate</b>
<b>Solubility In Water</b> Slight	
<b>Appearance and Odor</b> Clear liquid, solvent odor	

### Section IV Fire and Explosion Hazard Data

<b>Flash Point</b> 75 Deg. F. T.O.C.	<b>Flammable Limits</b> Extremely Flammable Spray	<b>LEL</b> N/A	<b>UEL</b> N/A
<b>Extinguishing Media</b>	Foam, dry media, CO2		