

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no.1218-0072

**Identify (Code Number, Name)**

2000975/14

Steel Coat

**Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, FL 33024**

Emergency Telephone Number  
1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 03/14/95

**HEALTH** 2  
**FLAMMABILITY** 2

**REACTIVITY** 1

Protective Equipment

B Goggles &amp; Gloves

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
1,1,1 Trichloroethane	71-55-6	350	350		39.0
Petroleum Distillates	64742-88-7	N.D.	N.D.		
Polyurethane Resin Solution	108-88-3	200	200		
Propellant Propane/Butane	74-98-6/106-87-8	1000	1000		

**Section III Physical Characteristics**

<b>Boiling Point</b>	Initial 160F	<b>Specific Gravity (Water =1)</b>	1.260
<b>Vapor Pressure</b>	45	<b>Melting Point</b>	N/A
<b>Vapor Density</b>	N/D	<b>Evaporation Rate</b>	N/A

<b>Solubility In Water</b>	Negligible
<b>Appearance and Odor</b>	Steel colored liquid characteristic odor

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
None up to 150F T.O.C.	Extremely Flammable	N/A	N/A

**Extinguishing Media** Foam, dry chemical, carbon dioxide