Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)
8800920 **Total Kill**

Section 1 Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 05/11/95

HEALTH 2
FLAMMABILITY 2
REACTIVITY 0

Protective Equipment
B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Fuel Oil	64741-44-2	NE	NE	NA	
NE - Not established					
NA - Not available					

Section III Physical Characteristics

Boiling Point	>350 deg F	**Specific Gravity (Water =1)**	0.850
Vapor Pressure	1-10MM Hg @ 100 deg. F	**Melting Point**	NA
Vapor Density	Not determined	**Evaporation Rate**	Not determined

Solubility In Water	Negligible
Appearance and Odor	Light amber, Kerosene odor.

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
130 deg. F (min) TCC Combustible		0.7	5.0

Extinguishing Media	Only UL approved class B fire extinguishing media such as foam, CO2, Halon 1211 or dry chemical. Water spray should be used only by qualified fire fighting personnel.