

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2200780/16

True Open Gear Lube Kwik Dri

Section 1 Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 06/29/98

HEALTH 1
FLAMMABILITY 4
REACTIVITY 0
Protective Equipment
B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	84741-66-8	400 ppm	400 ppm	No	10-20
Propylene Glycol Monomethyl Ether	107-98-2	100 ppm	100 ppm	No	05-10
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm	No	40-60

Section III Physical Characteristics

Boiling Point	~200 deg F	Specific Gravity (Water =1)	@ 75 deg F: 0.853
Vapor Pressure	(can/psig @ 70 deg F): 55	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A
Solubility In Water	Slight		
Appearance and Odor	Black, viscous, tacky liquid, solvent odor		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
Concentrate: 60 deg F (T.O.C.)	Extremely flammable spray		
Extinguishing Media	Foam, CO2, Dry Media		