

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

**Identify (Code Number, Name)**

2200175/17

V M R

**Section 1 Manufacturer's Name**

Emergency Telephone Number  
1-800-228-5635

**HEALTH** 1  
**FLAMMABILITY** 4

**Applied Research, Inc.**

Telephone # For Information

**REACTIVITY** 1

7367 Davie Rd. Ext

1-800-253-3500

Protective Equipment

Hollywood, Fl 33024

Date Prepared: 10/11/95

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Toluene	108-88-3	100 ppm	100 ppm		40-60
Diacetone Alcohol	123-42-2	50 ppm	50 ppm		05-10
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm		05-10
Sorbitan Monolaurate	N/D	N/E	N/E		01-05
Liquified Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		10-20

**Section III Physical Characteristics**

Boiling Point	N.D.	Specific Gravity (Water =1)	@ 75 deg. F; 0.935
Vapor Pressure (Can) psig @ 70 deg. F:	45	Melting Point	
Vapor Density	>1	Evaporation Rate	
Solubility In Water	Emulsion		
Appearance and Odor	Creamy white jel, Mild Odor.		

**Section IV Fire and Explosion Hazard Data**

Flash Point	Flammable Limits	LEL	UEL
(Concentrate) 64 deg. F (TOC)	Extremely flammable spray		

Extinguishing Media	Foam, CO2, Dry media.
---------------------	-----------------------