

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200990/11

White Ease "A"

Section 1 Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number

1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 02/13/97

HEALTH 2**FLAMMABILITY** 4**REACTIVITY** 0

Protective Equipment

B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64741-66-8	400 ppm	400 ppm		20-40
Lithium Grease	N/A	N/E	N/E		10-20
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		40-60

Section III Physical Characteristics

Boiling Point	~160 deg F	Specific Gravity (Water =1)	@ 75 deg F: 0.781
Vapor Pressure	(can/psig @ 70 deg F): 50	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A
Solubility In Water	Slight		
Appearance and Odor	Tan, opaque, viscous liquid. Solvent odor.		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
51 deg F (T.O.C.) - Concentrate only	Extremely Flammable Spray		